

BULLDOG

FOLDING TRAILERS

SPECIFICATIONS

WWW.BULLDOGFOLDINGTRAILERS.COM.AU



TYRES

8 INCH

- + Type 6 ply 71 N
- + Max load 345kg each at 6.2 BAR
- + Size 4.80 – 8
- + Speed rated 130 km/h

12 INCH (NOT STANDARD) AN ACCESSORY

- + Type 6 ply 72 N
- + Max load 355kg each at 3.5 BAR
- + Size 4.80 -12
- + Speed rated 130 km/h

Rim

- + Powder coated steel rim with integrated set 14 bearings. (LM44643/10)

COUPLING

- + Ball size B50 – X (50mm)
- + Static load 750kg
- + European standard - see photo



BUILD MATERIAL

- + Frame 235Q Mild steel (Yield strength 235MPa) Hot Dipped Zinc Plated
- + Fixings 304 Stainless steel

LIGHTS

- + LED combination light includes Number Plate Light

ELECTRIC CABLE

- + 5 core cable with plastic sheath

BULLDOG

FOLDING TRAILERS

SPECIFICATIONS

[WWW. BULLDOGFOLDINGTRAILERS.COM.AU](http://WWW.BULLDOGFOLDINGTRAILERS.COM.AU)

ELECTRICAL CAR CONNECTER
+ As required. 7 pin flat. Standard

DIMENSIONS (BASE TRAILER)

- + Width unfolded - 1.6m
 - + Length unfolded - 2.4m
 - + Height unfolded – 0.525m
 - + Width folded – 0.65m
 - + Length folded - 1.4m
 - + Height folded - 0.52m
-

WEIGHT (WHEN SET UP IN EACH CONFIGURATION)

- + 60kg – single track
 - + 85kg double track
 - + 85kg Flat Top
 - + 100kg Box Top
-

MAX LOAD ON EACH TYPE OF SET UP

- + 390kg on a single track trailer. –
 - + 365kg combined weight on a double track trailer
 - + 365kg on a Flat Top
 - + 350kg on a Box Top
-

GTM of the Trailer

- + 450kg
-

