

BULLDOG

FOLDING TRAILERS

Specifications

WWW.BULLDOGFOLDINGTRAILERS.COM.AU



TYRES

8 INCH

- + Type 6 ply 71 N
- + Max load 345kg each at 6.2 BAR
- + Size 4.80 – 8
- + Speed rated 130 km/h

10 INCH

- + Type 6 ply 72 N
- + Max load 355kg each at 3.5 BAR
- + Size 5.00 – 10
- + Speed rated 130 km/h

RIM

- + Powder coated steel rim with integrated set 14 bearings. (LM44643/10)

COUPLING

- + Ball size B50 – X (50mm)
- + Static load 750kg
- + European standard - see photo



BUILD MATERIAL

- + Frame 235Q Mild steel (Yield strength 235MPa) Hot dipped galvanised
- + Fixings 304 Stainless steel

LIGHTS

- + Submersible LED combination light including number plate light.

ELECTRIC CABLE

- + 5 core cable with plastic sheath

BULLDOG

FOLDING TRAILERS

Specifications

WWW.BULLDOGFOLDINGTRAILERS.COM.AU

ELECTRIC CABLE

+ 5 core cable with plastic sheath

ELECTRICAL CAR CONNECTER

+ As required. 7 pin flat - Standard

DIMENSIONS

+ Width unfolded - 1.6m

+ Length unfolded - 3.75m - 1st Extension: 4.03m - 2nd Extension 4.3m (Max Ext for dinghies only)

+ Height unfolded – 0.525m

+ Width folded – 0.56m

+ Length folded - 1.4m

+ Height folded - 0.45m

WEIGHT

+ Trailer weighs 65kg when assembled.

+ Trailer weighs 45kg when mounted to the caravan (Extension bar and winch have been removed - 20kg)

+ Caravan Bracket weighs 5kg (new model)

MAX LOAD

+ 385kg when the Bulldog is set up to carry boats.

GTM

+ 450kg

ACCESSORIES – SOLD SEPARATELY

Kayak/Canoe Rails

Carry Cradles for Kayaks and Canoes

Inflatable Boat Accessory kit

Caravan Bracket

Spare Wheel Assembly - 8" or 10" available

Jet Ski Accessory kit (Available soon)

